# 6 Tonne Front Tip

# **KEY FEATURES & BENEFITS - MACH2260**



Powered by a 3.3L Yanmar turbo diesel engine fitted with a DPF to comply with EU stage V emission regulations, you benefit from 53.7 kW peak power, 295 Nm of torque and no AdBlue requirement.

Thwaites 6 Tonne machines are available in a range of configurations to suit your needs including:

- > 6 Tonne Power Swivel with Cab
- > 6 Tonne Front Tip with Cab
- > Power Swivel

A Spring Activated Hydraulic Release (SAHR) Handbrake, 5" screen displaying 150° around machine visibility, hi-vis steps, and twin LED beacons are fitted as standard, with LED road lights, mirrors and GPS speedo available as optional extras.

Safe, compliant and competitive.










Snap this QR code from your smart phone for more information


















# 6 Tonne Front Tip

# **DIMENSIONS & SPECIFICATIONS - MACH2260**

Thualtes F



Α	4475	N	3430
В	2354	P	4742
С	2230		
D	1610		
Е	2240		
F	2480		
G	370		
Н	1740		
<u> </u>	1235		
J	340		
K	520		
L	2505		
M	2320		

(mm)

Weight	Unladen Shipping	3960 kg 3836 kg
Capacities	Max safe load Heaped Struck Water	6000 kg 3400 litres 2525 litres 1925 litres

## **Engine**

- Yanmar 4TNV98CT, water-cooled, 4-cylinder, fuel injected turbo diesel with after treatment Diesel Particulate filter
- Power 53.7kW / 72 bhp at 2100 rpm
- > Torque 295Nm (217.5 lbs ft)

#### **Noise Levels**

> Operator's ear 84 LpA / airborne level 102 LwA

## Transmission

> Hydrostatic with high/low speed range, column mounted directional control lever and inching facility.

Speeds	Forward an 1 2	6.1 km/h	(3.7 mph) (14.4 mph)
Tyres	405/70 - 20 Load/Speed Index - 145 G		

#### **Brakes and Axles**

- > Totally enclosed multiplate oil-immersed discs mounted on both axles & auto wear adjustment
- > Hand operated parking brake (SAHR)

#### **Kinglink Chassis**

> Constructed from folded steel plate, with three point Kinglink giving articulation and oscillation for better stability, traction and safety on site

#### Skip

- > Hydraulically operated, 6 mm steel base plate
- > Skip mouth & sides reinforced with box sections

#### **Seating & Controls**

- Adjustable suspension seat with high-vis seat belt
- > Clear operators display unit contains all warning lamps

#### Service Access

- Lockable engine cover for ground level service points
- > Rear chassis panel can be hinged back on retainers

#### **Electrics**

- > Fuse & relay are housed on a central power distribution board
- Main harness is fully enclosed in solid conduit and incorporates the engine diagnostic port

### Steering and Hydraulics

- > Hydraulic power steering
- > Return line filtration for all services
- Hydraulic test point fitted as standard

Tank Capacities	Fuel Hydraulic	72 litres 50 litres
Turning Circle	12.6m	


#### **Standard Equipment**

- Camera and dashpanel monitor
- > LED beacons
- Fan guard
- > Reverse alarm

### **Optional Equipment**

- > Full LED road lighting incl. DRL (Daylight Running Lights)
- > Road mirrors
- > Wheel nut indicator
- > GPS speedometer





www.thwaitesdumpers.co.ul













