

Compact Telehandlers


TF30.9





PERFORMANCE AND FEATURES	TF30.9 G	TF30.9-115	
Performance			
Total unladen weight (kg)	7100	7200	
Maximum capacity (kg)	3000	3000	
Lifting height (m)	8,6	8,6	
Maximum reach (m)	5,7	5,7	
Maximum operating height (m)	5,8	5,8	
Maximum operating reach (m)	1,8	1,8	
Capacity at maximum height (kg)	1200	1200	
Capacity at maximum reach (kg)	650	650	
Lateral boom movement (mm)	-	-	
Tilting correction (%)	-	-	
Boom sections	3	3	
PowerTrain			
Turbo motor	KOHLER KDI 2504 TCR	DEUTZ TCD3.6	
Displacement/cylinders	2500/4	3600/4	
Engine Power (kW/HP)	55,4/75,1	85/115	
Anti-pollution technology	STAGE V, DOC+DPF	STAGE V, SCR+DPF+DOC	
Reversible fan	●	●	
Maximum speed (km/h)	40	40	
Fuel tank (l)	80	85	
AdBlue tank (l)	-	12	
Hydrostatic transmission	● - 2V	● - 2V	
EPD	●	Plus	
Auto-revving joystick	-	●	
Axles - Reducers	Axial, Epicyclic	Axial, Epicyclic	
Machine brakes	Dry disc	Dry disc	
Automatic parking brake	●	●	
Hydraulic			
Hydraulic pump	Gear	LS+FS	
Flow rate/pressure (l/min - bar)	98-210	125-210	
Hydraulic tank	85	85	
Hydraulic outlet at the top of the boom	●	●	
Rear hydraulic outlets	○	○	
Cab			
Cab configuration	ECO	ECO	
ASCS Adaptive Stability Control System	-	Light	
FOPS LIV II cab	●	●	
ROPS cab	●	●	
Cab commands	Electrohydraulic joystick	Electronic joystick	
Tilting Cab	-	-	
Reverse shuttle	Dual reverse	Dual reverse	
Configuration			
Cab suspension	-	-	
Boom suspension	○	○	
Suspension on axles	-	-	
Work headlights on cab	○	●	
Sun blind	○	○	
Tac-lock	●	●	
Provision for a platform	-	○	
Two floating forks	●	●	
Inching-Control	●	●	
Four-wheel drive	●	●	
Four-wheel steering	●	●	
Three steering modes	●	●	
Standard tyres	400/70-20	400/70-20	
Optional tyres	405/70-24, 400/70 24"	405/70-24, 400/70 24"	
Stabilisers	-	-	
Turret rotation	-	-	
Type approval as an agricultural tractor	○	○	
Approval with PNEUMATIC braking	-	-	
Approval with HYDRAULIC braking	○	○	
PTO	-	-	
3-point linkage	-	-	

- Not Available
● Standard
○ Optional




TF30.9

Dimensions



	TF30.9		
A (mm)	4330		
B (mm)	990		
C (mm)	2740		
D (mm)	600		
E (mm)	3910		
F (mm)	290		
H (mm)	2100		
M (mm)	1010		
P (mm)	2120 (2020 L)		
R (mm)	3930		
S (mm)	4660		
Z (mm)	850		



Your Merlo dealer



MERLO S.P.A.

Via Nazionale, 9

12010 S. Defendente di Cervasca, (Cuneo) Italia

Tel. +39 0171 614111

Fax +39 0171 684101

info@merlo.com

www.merlo.com

